

Speed Queen®

MULTI-HOUSING

Electronic Homestyle
Rear Control
Washers and Dryers



BUILT FOR RELIABLE PERFORMANCE.

100 years. It's a long time for any company to be at the forefront of an industry. It's given us a long time to refine our craft, down to the smallest detail. For more than a century, Speed Queen has built a legacy on providing proven premium quality laundry equipment that stands up to any challenge. We make no compromises in performance. We refuse to be outdone in reliability and efficiency. And our commitment to quality is matched only by our commitment to you.

The result is the most reliable machine in the industry. We believe that strength comes from within. That's why every technical feature and every component of a Speed Queen machine is built specifically for the commercial environment. Our world-class test lab rigorously pushes our products far beyond the conditions they're likely to ever face. We work hard at every point of our manufacturing process to ensure that our machines reflect that belief.

Electronic homestyle control is designed for durability and easy operation with attractive selection buttons and cycle status indicator lights. Speed Queen front load laundry products have met every design standard to be 100% ADA compliant.



TOP LOAD WASHER

Durable stainless steel tub becomes smoother with each use, so it won't pill, snag or fray clothes. Comes with a lifetime warranty.

710 RPM final spin speed extracts more water from loads reducing the energy costs associated with long drying times.

Advanced suspension system eliminates the possibility of an unbalanced load issue. Rear self-leveling legs maximize smooth and quiet operation on all floor types.

PolyTuff® curved four-vane polypropylene agitator with high vanes and extra long 210° agitation stroke delivers superior washability for all load sizes.




FRONT LOAD WASHER

Revolutionary balancing technology redistributes even the most unbalanced loads for consistent cycle times, minimized vibration and reduced noise.

Increase spin speed extracts 440 G-Force to maximize moisture removal, helping to minimize dry times.

20% increase in capacity with improved water usage for superior washability, increased customer satisfaction and lower utility bills.

Heavy-duty design features like a rugged suspension system and stainless steel washtub and outer drain tub to deliver long-lasting performance.



Larger door opening - extra wide 15.5" (394 cm) for easy loading and unloading of clothes.

Redesigned four-compartment soap dispenser for simplified use and cleaning.

SINGLE LOAD DRYER

Speed Queen's dryer, defined by its simplicity and performance, provides everything you need to get the job done – and nothing you don't. The single load dryer combines heavy-duty construction with reliable operation proven to stand the test of time.



Designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road. Our cabinet design maintains the perfect balance of heat, airflow and tumble action for optimal performance and efficiency.

Durable galvanized steel cylinder. Superior drying convenience including the industry's largest door opening 2.06 sq. ft. (1914 cm²). Efficient dryer heating with 25,000 BTU (gas models) and up to 5,350 Watts (electric models). Speed Queen dryers offer some of the fastest drying times in the industry. The upfront lint filter is secured and easy to clean.



STACK DRYER

The Speed Queen stack dryer offers the same great features as the single load dryer. Two commercial dryers in the space of one, both operating independently, including independent controls for optimum usage. Same great features as the front control dryer for superior drying convenience. Available with see-through or solid door models. (Solid door is reversible). Bottom dryer is ADA compliant.



ELECTRONIC HOMESTYLE CONTROL COMMERCIAL WASHER & DRYER SPECIFICATIONS

MODELS	TOP LOAD WASHER	FRONT LOAD WASHER	SINGLE DRYER	STACK DRYER/DRYER
Available Control Location	Rear	Rear	Rear	Front
Capacity - lb (kg)	16 (7.3)	21.5 (9.5)	18 (8.2)	18 (8.2) ea
Cylinder Volume - cu. Ft. (liters)	3.26 (92.3)	3.42 (96.8)	7.0 (198)	7.0 (198) (ea)
Width - in (mm)	25 5/8 (650)	26 7/8 (683)	26 7/8 (683)	26 7/8 (683)
Depth - in (mm)	28 (711)	27 3/4 (704)	28 (711)	29 (737)
Height - in (mm)	43 (1092)	43 (1092)	43 (1092)	78 3/16 (1986)
Spin Speed G-Force (RPM)	150 (710)	440 (1200, 800, 500)	N/A	N/A
Motor Size - HP (kw)	1/2 (0.37)	Variable Speed Induction 0.9 (0.67)	1/3 (0.25)	1/3 (0.25)
Water Consumption per Cycle - g (l)*	24.3 (92.2)	11.7 (44.3)	N/A	N/A
WF (Water Factor)	8.4 (1.12)	3.8 (0.52)	N/A	N/A
MEF (Modified Energy Factor)	1.29 (47.89)	2.98 (84.48)	N/A	N/A
Available Heat Sources	N/A	N/A	Gas or Electric	Gas or Electric
Available Heating Element (Electric W)	N/A	N/A	4750W @ 208V	4750W @ 208V 5350 @ 240V
Gas Inlet Connection - in (mm)	N/A	N/A	3/8 (9.5)	3/8 (9.5)
Gas Consumption - BTU/Hr	N/A	N/A	25,000	25,000
Exhaust Outlet Dia. - in (mm)	N/A	N/A	4 (102)	4 (102)
Exhaust Airflow - cfm (liters/sec)	N/A	N/A	220 (105)	220 (105)
Available Water Temperatures	Hot, Warm, Cold	Hot, Warm, Cold	N/A	N/A
Available Cycles	Heavy Duty, Normal Eco, Perm Press Delicate, Rinse & Spin, Spin Only	Heavy Duty, Normal Eco, Perm Press Delicate, Rinse & Spin, Spin Only	Regular, Delicate, Perm Press Time Dry, Quick Dry, Fluff Up	Regular, Delicate, Perm Press Time Dry, Quick Dry, Fluff Up
Water Pressure - PSI (Bar)	20-120 (1.4/8.3)	20-120 (1.4/8.3)	N/A	N/A
Cycle Indicator Lights	Yes	Yes	Yes	Yes
Cylinder Finish	Stainless Steel, Porcelain	Stainless Steel	Galvanized	Galvanized
Available Colors	White	White	White	White
Door Type (Solid Window)	N/A	Window	Solid	Solid or Window
Drain	Pump	Pump	N/A	N/A
Available Electrical Requirements (Voltage/Hz/Ph - Circuit Amperage)	120/60/1 - 15 Amp	120/60/1 - 15 Amp	Electric: 120/240/60/1 - 30 Amp* Gas: 120/208/60/1 - 30 Amp	Electric: 120/240/60/1 - 30 Amp* 120/208/60/1 - 30 amp Gas: 120/208/60/1 - 30 Amp
Net Weight - lb (kg)	190 (86)	253 (115)	Electric 135 (61) Gas 140 (64)	Electric 265 (120) Gas 275 (125)
Shipping Weight - lb (kg)	210 (95)	273 (124)	Electric 145 (66) Gas 150 (68)	Electric 280 (127) Gas 290 (132)
Shipping Width - in (mm)	27 1/2 (699)	29 (737)	29 (737)	29 (737)
Shipping Depth - in (mm)	30 (762)	32 3/4 (832)	32 3/4 (832)	32 3/4 (832)
Shipping Height - in (mm)	44 1/4 (1124)	45 1/2 (1156)	45 1/2 (1156)	80 (2032)
Available Agency Approvals	cULus	cULus	Electric: cULus, Gas: cCSAus	Electric: cULus, Gas: cCSAus

NOTE: Each stack dryer pocket requires its own separate power cord. | Stack washer/dryer requires two power cords - One for washer, one for dryer.

* Electric dryers come equipped for 240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008. Printed in the USA.

